KP250 DIGITAL DEADBOLT



DIMENSIONS



STANDARD SPECIFICATIONS

Door Prep	Cross bore: 2-1/8" Edge bore: 1"	Dimensions	Interior Unit: 7-1/2" x 2-7/8" x 1-3/4" (H x W x D) Exterior Unit: 5-1/8" x 3-1/8"	
	Latch face: 1" x 2-1/4"	Door Thickness	1-3/8" ~ 2" door	
Backset	Fits 2-3/8" and 2-3/4"	Power 6V - 4 AA Batteries, Not Included. (Estimated battery life, 1-year)		
Strike	9113 & 9117	Warranty Period	1 Year for Electronic Components	
Throwbolt	1" for maximum security	Passcode 4 to 10 digits, Maximum of 6 Passcodes supported		
Cylinder	KW1 5-pin cylinder Standard. SC1 optional Packed KD	No. of Remotes Supported	Includes 1 Remote Maximum 5 supported per unit	

Model	Function	WT/CTN	CTN QTY		US15 Satin Nickel	US12P Tuscany Bronze
KP250	Electronic Deadbolt	20 Lbs	6 Pcs	Item No.	311704	311705
 Description			QTY		Item No.	
KP250 Programable Remote Control			Each		311700	

